

Features		DT750	DT730	DT710
Display	Display size	Touch screen 320x240 dot TFT (65536 colour) LCD backlight	224x96 dot matrix grayscale LCD backlight Optional 2nd display for DESI-less	6DE: 168x41 dot matrix B/W LCD, not backlight
	Characters x Lines	Supports 2 proportional font sizes, 12 and 16 dot	Alphanumeric: 28x6 (7x16font) or 34x8 (6x12font) DESI-less line key display area: 12x1 & icon/line key	6DE: 28x3 (6x12font)
	Tilttable	Yes	Yes	N/A
Keypad	Backlit keypad	Yes	Yes	N/A
	Line keys	LCD	12, 24, 32 DESI-less: 8 x 4 pages	2, 6
	Softkeys	4, help, exit	4, help, exit	4, help, exit (only on 6DE)
	Cursor keys	Yes	Yes	No
Built In Applications	XML Open Interface	Yes	Yes	Yes (limited)
	Personal directory	Yes	Yes	Yes (speed dial)
	System directory	Yes	Yes	No
	Corporate directory	Yes	Yes	No
	Call history	Yes	Yes	Yes (last number)
Sound	Full duplex hands-free	Yes	Yes	Yes
	Downloadable ring tone	Yes	Yes	N/A
	Downloadable hold music	Yes	Yes	N/A
	CODEC	G.711, G.729A, G.722 (the latter not on DT710)		
Network	NAT traversal support	Yes	Yes	Yes
	VPN access	Yes	Yes	Yes
	Power	802.3af or AC	802.3af or AC	802.3af or AC
Optional Adapters	DSS	Yes	Yes	N/A
	Recording adapter	Yes	Yes	N/A
	PSTN survivable adapter	Yes	Yes	N/A
	AC adapter (option)	27V 750mA	27V 750mA	27V 750mA
Security	Authentication	Yes	Yes	Yes
	Encryption	Yes	Yes	Yes
	Security button	Yes	Yes	Yes
Maintenance	Auto-Configuration	Yes	Yes	Yes
	Network Management:	Yes	Yesx	Yes
Other	Headset support	Yes	Yes	No
	Wall mountable capability	Yes	Yes	Yes
	Integrated 2-port Ethernet switch	Yes	Yes	Yes
Characteristics	Dimension (wxdxh)	227x250x112 mm	12D/24D: 179x258x112 mm 32D (24D+8LK): 205.8x258x112 mm DESI-less: 179x264x112 mm	2E: 179x225x112 mm 6DE: 179x225x112 mm
	Weight (approx. lbs.)	1.6 kg	12D/24D: 1.2 kg 32D (24D+8LK): 1.3 kg DESI-less: 1.3 kg	2E: 1.0 kg 6DE: 1.1 kg
	Power (excl. options) (Ethernet IEEE802.3af)	32D: 6.49 W	12D/24D: 6.49 W DESI-less: 6.49 W	2E: 3.84 W 6DE: 3.84 W
Compliance	EMC:	The Desktop IP Terminals carry a CE mark and comply with: EMC: EN55022 Emission EN55024 Immunity EN61000 Powering		
	Safety:	EN60950-1		
	Transmission and signalling:	TIA/EIA 810-A		

NEC Representative:



COM-IT Solutions Ltd
126 Cobham Road
Fetcham t 0844 257 5000
Leatherhead f 0844 257 5001
Surrey KT22 9JS e info@com-its.com

UNIVERGE360 is NEC's approach to unifying business communications. It places people at the center of communications and delivers on an organization's needs by uniting infrastructure, communications and business.



NEC Infrontia Limited

Innovation House, Mere Way, Ruddington Fields Business Park,
Ruddington, Nottingham NG11 6JS

Tel: +44 (0) 115 969 5700

Fax: +44 (0) 115 931 5970

Web: www.neci.co.uk

This publication provides outline information only which (unless specifically agreed by NEC Infrontia in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. NEC Infrontia reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service. E&OE.